## Port



## Specifications

| Feature               | Description   |
|-----------------------|---|
| AUDIO                 |   |
| Sound quality         | THD+N<0.009%, 20 Hz-20 kHz  |
| Line in               | Analog (RCA), auto-detecting  |
| Line out              | Analog (RCA), digital (coaxial)   |
| NETWORKING            |   |
| Wireless connectivity | Using Sonos S2: Connects to WiFi network with any 802.11a/b/g/n 2.4 or 5 GHz broadcast-capable router.  Using Sonos S1: Connects to WiFi network with any 802.11b/g 2.4 GHz broadcast-capable router. 802.11n only network configurations are not supported—you can either change the router settings to 802.11b/g/n or connect a Sonos product to your router. |
| Ethernet port         | Two 10/100Mbps Ethernet ports.  You can plug a Sonos product directly into your router if your WiFi is unstable.  |
| GENERAL               |   |

| Feature                | Description  |
|------------------------|--|
|                        | Auto-switching 100 - 240V ~ 50-60 Hz 1A<br>AC universal input  |
| Power supply           | Output: 12.0 VDC, 1.0 A, 12.0 W Average active efficiency: 84.2% Efficiency at low load (10%): 78.7% No-load power consumption: 0.06 W |
| Dimensions (H x W x D) | 1.6 x 5.4 x 5.4 in. (41 x 138 x 138 mm)  |
| Weight                 | 1 lb (.47 kg)  |
| Operating temperature  | 32° to 104° F (0 to 40° C)   |
| Storage temperature    | -4° to 158° F (-20° to 70° C)  |
| Product finish         | Black  |
| Package contents       | Sonos Port, power cord, RCA cable, and Quickstart Guide  |

<sup>\*</sup> Specifications subject to change without notice.